



PVBS32-SPOOL-O40/F40/F40/O65-CV

157B9538

Model Code:  
SVSSPOL0I40404065FF0F0FDD5PP4X00LLTP551000CS0

Where to buy

Product specifications

Characteristic	Value	Description
Spool Interface	0I	PVB32 LS Shuttle
A->T Flow Rate	40	40
P-> A Flow Rate	40	40
P-> B Flow Rate	40	40
B->T Flow Rate	65	65
A->T Control Type	F	Flow
P->A Control Type	F	Flow
Pressure Control P->A	0	N/A
P->B Control Type	F	Flow
Pressure Control P->B	0	N/A
B->T Control Type	F	Flow
A->T Function in Neutral	D	Drained (Throttle Open)
B->T Function in Neutral	D	Drained (Throttle Open)
Spool Deadband	5	1.5
Spool Characteristic A	P	Progressive
Spool Characteristic B	P	Progressive
Pilot Pressure Neutral	4	4.0 bar
Pilot Pressure Full Stroke	X	5.5 bar
Nominal Diameter	S	Standard
Minimum Float Position	0	N/A
Float Direction	0	N/A

Characteristic	Value	Description
Nominel Max Position A	L	7.2
Nominel Max Position B	L	7.2
Spool Option A	T	Tensionbar
Spool Option B	P	Plug
Product Category	1	Standard Part
Primer	0	N/A
Marking	0	N/A
Ex Application	0	N/A
Certification	CS	ISO13849 Compliant
Spool Data	0	N/A
Marking	0	N/A
Spool Deadband		1.5

General specifications

Characteristic	Value
Proposition 65	Cancer and Reproductive Harm

For the most current information and other product assets, please use this link to visit the product page on Danfoss PowerSource [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.