



Ordering data: 1LE1003-1CB23-4AA4

Motor type: 1AV3132B

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%]			Power factor at ... load			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_A/I_N	T_T/T_N	T_B/T_N	
400	Δ	50	7.50	- / -	14.30	1470	48.7	90.4	90.4	89.4	0.84	0.80	0.71	7.4	2.4	3.5	IE3
690	Y	50	7.50	- / -	8.30	1470	48.7	90.4	90.4	89.4	0.84	0.80	0.71	7.4	2.4	3.5	IE3
460	Δ	60	8.60	- / -	14.20	1770	46.4	89.5	89.5	88.5	0.85	0.81	0.73	7.5	2.1	3.5	IE2

IM B3 / IM 1001		FS 132 M	64 kg	IP55	IEC/EN 60034	IEC, DIN, ISO, VDE, EN
-----------------	--	----------	-------	------	--------------	------------------------

Mechanical data		Terminal box	
Sound pressure level 50 Hz/60Hz (load)	64 db(A) 68 db(A)	Terminal box position	top
Moment of inertia	0.046 kg m ²	Material of terminal box	Aluminium
Bearing DE NDE	6208 2ZC3 6208 2ZC3	Type of terminal box	TB1 H00
Bearing lifetime	40000 h	Contact screw thread	M4
Lubricants	Esso Unirex N3	Max. cross-sectional area	6.0 mm ²
Regreasing device	No	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Grease nipple	- / -	Cable entry	2xM32x1,5
Type of bearing	Preloaded bearing NDE	Cable gland	2 plugs
Condensate drainage holes	No	Environmental conditions	
External earthing terminal	No	Ambient temperature	-20 °C - +40 °C
Vibration class	A	Altitude above sea level	1000 m
Insulation	155(F) to 130(B)	Special design	
Duty type	S1		
Direction of rotation	bidirectional		
Frame material	aluminum		
Data of anti condensation heating	- / -		
Coating	Special paint finish		
Color	RAL7030		
Motor protection	(A) without (Standard)		
Method of cooling	IC411 - self ventilated, surface cooled		