

HIAB OIL TANKS 150-400 LITRE

Technical data	150	150	200	250	300	400
Steel, powder coated (grey)	3391582	3391591	3391604	3391612	3391621	3391710
Stainless steel, electropolished	3391639	3391647	3391655	3391663	3391671	3391728
Aluminium	3395090	3395103	3395111	3395120	3395138	-
Net volume (litres)	150	150	200	150	300	400
Gross volume (litres)	185	185	240	50	340	455
Tank size - H1 / D1 / L1 (mm)	550/600/620	550/600/620	550/600/795	550/600/1000	550/600/1125	550/600/1450
Tank size, total (mm)	690/665/650	690/665/650	690/665/825	690/665/1030	690/665/1155	690/665/1481
Weight (kg) steel / stainless steel / aluminium	43/47/34	45/49/36	50/57/40	54/63/43	63/74/50	73/87/-
Return line filter capacity (l/min)	180	280	280	280	280	280
Filtration absolute	10	10	10	10	10	10
Return line filter inlet	2 pcs ISO-G 1"	1 pc ISO-G 1" and 2 pcs ISO-G 1 1/2"	1 pc ISO-G 1" and 2 pcs ISO-G 1 1/2"	1 pc ISO-G 1" and 2 pcs ISO-G 1 1/2"	1 pc ISO-G 1" and 2 pcs ISO-G 1 1/2"	1 pc ISO-G 1" and 2 pcs ISO-G 1 1/2"
Return line filter outlet	SAE 3" for Ø 50 (2") and Ø 63 (2 1/2")	SAE 3" for Ø 50 (2") and Ø 63 (2 1/2")	SAE 3" for Ø 50 (2") and Ø 63 (2 1/2")	SAE 3" for Ø 50 (2") and Ø 63 (2 1/2")	SAE 3" for Ø 50 (2") and Ø 63 (2 1/2")	SAE 3" for Ø 50 (2") and Ø 63 (2 1/2")

All tanks are delivered with: Return filter, Level indicator, Air breather, Chassis consoles, Plugs for oil tank, Suction connection.

Technical drawing

