

Code (SAP No.)	3505449
Item no	69101
Description	Remote Control System G2 Mini Linear 6 11-564

System description:

24 VDC Supply.

Radio communication at 434 MHz (ISM-band), cable control option also available.

6 bi-directional linear levers for control of 6 PWM outputs A/B.

All PWM outputs programmable for individual adjustments of speeds.

6 digital outputs available thru left switch panel for engine control:

-RPM On, Off or AUTO (8 seconds deactivation delay).

-Engine Start / Stop

-RPM+ / RPM-

-One optional digital output provided.

DV-output with auto off delay when no analog function is active (0.5 seconds).

PWM outputs provided with JPT connectors marked 1A - 6B.

DV-output provided with Hirschmann GDM3009 connector marked DV.

Supply and digital outputs provided with 3 meter cables for terminal connection.

Provided also with standard 10 meter cable available for optional cable control, emergency stop button, 24VDC Battery charger, 2 x Standard Batteries and a carrying strap for the Portable Control Unit.


Scope of delivery:

Code (SAP No.)	Description:
3505464	G2 Portable Control Unit Mini Linear 6 11-564
3505475	G2 Central Unit 24VDC PWM
3505477	Standard supply cable kit
3505478	Valve connection kit PWM JPT 1A-6B
3505481	Standard battery charger
3505480	Standard battery pack (x2)
3505488	Standard 10 meter control cable
3505507	Standard emergency stop
3505490	Standard carrying strap
3505508	Instruction manual RC400 G2 (English)