



**“F” TYPE COIL**



**DESCRIPTION**

3/4 inch (19 mm) I.D. Coil.

Color identification: silver metallic envelope

**FEATURES**


One piece encapsulated design that is:

- Immersion proof
- No external metal shell
- Internal arc suppression diode available on request


**COIL SPECIFICATION**

Wattage	20 Watts Nominal
Duty Rating	Continuous Duty ±10% rated voltage at 120°F (49°C) ambient
Min Current for Actuation	80% of rated current at room temperature
Magnet Wire Class	H (200°C)
Heat insulation Class	H (180°C)
Ambient Temperature Range	-30° to 60°C
Protection degree	Up to IP 65 (with connector and suitable seals)
Encapsulation Material	Glass filled polyester, resistant to moisture, caustic solutions, fungus and vibration


**FHC**



**FDI**



**FJT**



**ORDERING INFORMATION**

<b>F</b>	-	-	-	
<b>TERMINATIONS</b>				<b>VOLTAGE</b>
DIN 43650 (Hirschmann)	<b>HC</b>	<b>12</b>		12 VDC / 1.66 A
AMP Junior Timer - Integral	<b>JT</b>	<b>24</b>		24 VDC / 0.83 A
Deutsch - Integral DT04-2P	<b>DI</b>			

Approximate Coil Weight: .49 lbs (.22 kg)

**WARNING:** the specifications/application data shown in our catalogs and data sheets are intended only as a general guide for the product described (herein). Any specific application should not be undertaken without independent study, evaluation, and testing for suitability.

W7 / 2017



4484 Boeing Drive Rockford, IL 61109 • USA • Phone +1 (815) 397-6628 • Fax +1 (815) 397-2526  
 mail: delta@delta-power.com • www.delta-power.com



Via Malavolti, 36 • 41122 Modena • ITALY • Phone +39 (059) 254895 • Fax +39 (059) 253512  
 mail: tecnord@tecnord.com • www.tecnord.com