

**Vickers****859160****Industrial Valves - DG4V 3 0B M U H7 60****Model Code:** DG4V-3-0B-M-U-H7-60**Modify Configuration**

Product Specifications

Feature	Code	Description
SEAL TYPE	—	(0) VITON
VALVE TYPE	DG4V	(DG4V) SOL. OPERATED SUB PLATE MOUNTED DCV, 350 BAR AT PORTS A, B & P
INTERFACE	-3	(3) ISO/DIN 4401-AB-03, SIZE 3 INTERFACE
PERFORMANCE	—	(0) HIGH PERFORMANCE
SPOOL TYPE	-0	(0) OPEN CENTER (ALL PORTS)
SPRING ARRANGEMENT	B	(B) SPRING CENTERED, SINGLE SOLENOID
BUILD ORIENTATION	—	(0) STANDARD BUILD
MANUAL OVERRIDE	—	(0) PLAIN OVERRIDE IN SOLENOID ENDS ONLY
SOLENOID IDENTIFICATION	-M	(M) FLAG WITH STANDARD BUILD AS PER ANSI B93.9
SPOOL MONITORING SWITCH	—	(0) NO SPOOL POSITION MONITORING SWITCH
COIL TYPE	-U	(U) ISO4400, DIN43650 CONNECTOR
SOLENOID INDICATOR LIGHT	—	(0) NO SOLENOID INDICATOR LIGHT
DIODE	—	(0) NO DIODE
COIL VOLTAGE	-H	(H) 24V DC 30 WATT
TANK PORT RATING	7	(7) 210 BAR (3000 PSI) FOR DC HIGH PERFORMANCE MODELS
DESIGN CODE	-60	(60) DESIGN NUMBER