

Loglift Jonsered Grapples








www.dzwingi.net.pl

LOGLIFT
JONSERED

Loglift Jonsered

X 43

X 53




The X series grapples, X 43 and X 53 are eminently suitable for mid-sized truck loaders for loading pulpwood and logs.

Loglift Jonsered


FX 26

FX 36




FX 42



FX 26
FX 36



FX 42



The FX series is designed to withstand the demanding use of forestry machines. The FX 26 and FX 36 are suited for forestry cranes and lightweight truck loaders. The FX 42 is suited for heavy forestry machine and skidder cranes.

Loglift Jonsered

Technical data

	Holding area	Max. load	Max. working pressure	Jaw pressure (jaw against jaw)	Weight	F. Max grip width	G. Min. diameter	H. Height, jaw against jaw	I. Height, opened	J. Height, closed	K. Width, closed	L. Width outer jaw	M. Width, inner jaw	N. Max. width
Model	m ²	kg	MPa	kN/MPa	kg	mm	Ø mm	mm	mm	mm	mm	mm	mm	mm
PX 20	0,2	3000	20	12/20	135	1100	40	915	880	590	840	145	40	245
PX 40	0,4	4000	25	11,9/25	185	1600	80	985	840	585	1045	170	122	412
RX 31	0,35	4000	25	14,1/25	200	1640	100	960	805	520	1010	456	376	486
RX 51	0,5	5000	23	17/23	265	1960	165	1055	800	660	1035	560	480	590
FX 26	0,25	4000	25	14,1/25	165	1485	105	860	745	540	825	394	346	422
FX 36	0,35	4000	25	13,1/25	175	1570	105	925	785	570	935	394	346	422
FX 42	0,4	6000	24	19/24	250	1825	120	1040	855	635	975	520	460	548
X 43	0,4	5000	23	18/23	220	1825	120	1040	855	635	980	500	450	528
X 53	0,5	5000	23	17/23	225	1985	165	1075	810	670	1040	500	450	528
TX 56	0,5	9000	27	21,7/27	340	2010	120	1165	995	675	1150	530	464	558
TX 56 B	0,5	9000 ^{*)}	27	21,7/27	345	1975	120	1165	1015	675	1150	530	464	558
TX 86 B	0,8	9000 ^{*)}	27	19,1/27	360	2260	175	1415	1180	750	1605	530	464	558
TX 811 B	0,8	9000 ^{*)}	27	19,1/27	455	2260	175	1415	1145	750	1605	1000	930	1000
RC 30	0,35	4000	25	12,5/25	235	1640	130	960	805	565	1000	456	376	484
RC 50	0,5	5000	23	17/23	350	1960	165	1065	800	665	1035	560	480	588
RC 50-67	0,5	5000	23	17/23	405	1960	165	1065	800	665	1035	560	480	588
^{*)} Max. load down 2000 kg														

We reserve the right to make changes. Illustrations, drawings and data are not always in accordance with the latest version or standard model in production. The models in the pictures may present special equipment or colours.