

Transmitter – The models



Pocket 3

A1003000090

Transmitter G5 pocket 3
with 3 push buttons



Pocket

A1003000070

Transmitter G5 pocket 8
with 8 push buttons



Pocket 6

A1003000100

Transmitter G5 pocket 6
with 6 push buttons

Pocket Fn

A1003000071

Transmitter G5 pocket Fn
with 6 push buttons and
Fn/stop buttons

G5 Transmitters Pocket



- Light weight, water and impact resistant.
- 3-8 pushbuttons.
- 5 LED for machine and status feedback.
- Powered with 3 AAA batteries.
- Belt clip for convenient attachment on the operators belt.

G5 Transmitters Pocket technical data



- Platform G5
- Power Supply 3 x AAA batteries
- IP-Class IP67
- LED for feedback From left: Green, Yellow, Yellow, Yellow, Red
- Radio Frequency 2.4 GHz using frequency jumping technology
- Operating range > 100m > ~330 ft
- Current consumption 10-60mA (depending on the number of LED used)
- Operating time Several months (depending of usage and application)
- Approvals TR05 Integrated duplex radio ISM-band, R&TTE, FCC and IC approved
- Ambient Temperature -25°C to +70°C ~ -15°F to +160°F
- WxHxD 67 x 115 x 38 mm ~ 2.6 x 4.5 x 1.5 in
- Weight 160 g (including batteries) ~ 0.35 lbs (including batteries)