



| TECHNICAL DATA | |
|-------------------------------------------------------------------------------------------------------------------------|------------|
| Weight: | 0.25 kg |
| HEAT INSULATION CLASS H: | |
| 356°F | (180°C) |
| Ambient temperature range: | |
| -22+122°F | (-30+50°C) |
| Available on request: | |
| Different Voltages - Different connectors. | |
| Inlet voltage fluctuations must not exceed ± 10% of nominal voltage to obtain correct operation and long life of coils. | |

| X | Power (W) |
|-----|-----------|
| 260 | 26 Watt. |
| | |
| | |
| | |
| | |
| | |

| Y | Connections |
|---|---------------------|
| F | DEUTSCH DT04-2P (V) |
| | |
| | |
| | |
| | |

| Z | Voltage (V) | Resistance (Ω) | Current (A) | |
|---|-------------|----------------|-------------|----------|
| | Nominal | 20~25 °C | Cold Coil | Hot Coil |
| E | 12V DC | 5.5±7% | 2.05 | 1.43 |
| D | 24V DC | 21.0±7% | 1.10 | 0.75 |
| J | 28V DC | 29.9±7% | 0.92 | 0.62 |
| M | 14V DC | 7.5±7% | 1.83 | 1.24 |
| | | | | |
| | | | | |
| | | | | |