

		TYPE							
		F = FILTER COMPLETE	F	F	F	F	F		
		B = FILTER HOUSING	B	B	B	B	B	ELEMENT	E
P	B	FAMILY, SIZE & LENGTH						FAMILY SIZE & LENGTH	P B
			11	12	13	21	22		
		PORT TYPE							
		B = BSP - thread	B	B	B	B	B		
		N = NPT - thread	N	N	N	N	N		
		S = SAE - thread	S	S	S	S	S		
		F = SAE Flange 3000 psi	-	-	-	F	F		
		G = SAE Flange 6000 psi	-	-	-	G	G		
		PORT SIZE							
		04 = 1/2" (N04 not available)	04	04	04	-	-		
		06 = 3/4"	06	06	06	06	06		
		08 = 1" (G08 not available; F08 for PB2+ only)	-	-	-	08	08		
		BYPASS VALVE							
		W = without	W	W	W	W	W		
		C = 600 kPa (6 bar)	C	C	C	C	C		
		R = reverse flow valve	-	-	-	R	R	} on request only	
		P = reverse flow + bypass valve	-	-	-	P	P		
		SEALS						SEALS	
		N = NBR Nitrile	N	N	N	N	N	N = NBR	
		F = FKM Fluoroelastomer	F	F	F	F	F	F = FKM	
		FILTER MEDIA						FILTER MEDIA	
		FA = fiber 5 μm(β) β>1.000 Δp 2MPa (20 bar)	FA	FA	FA	FA	FA	FA = fib. 5 μm(β) 20 bar	
		FB = fiber 7 μm(β) β>1.000 Δp 2MPa (20 bar)	FB	FB	FB	FB	FB	FB = fib. 7 μm(β) 20 bar	
		FC = fiber 12 μm(β) β>1.000 Δp 2MPa (20 bar)	FC	FC	FC	FC	FC	FC = fib. 12 μm(β) 20 bar	
		FD = fiber 21 μm(β) β>1.000 Δp 2MPa (20 bar)	FD	FD	FD	FD	FD	FD = fib. 21 μm(β) 20 bar	
		HA = fiber 5 μm(β) β>1.000 Δp 21MPa (210 bar)	HA	HA	HA	HA	HA	HA = fib. 5 μm(β) 210 bar	
		HB = fiber 7 μm(β) β>1.000 Δp 21MPa (210 bar)	HB	HB	HB	HB	HB	HB = fib. 7 μm(β) 210 bar	
		HC = fiber 12 μm(β) β>1.000 Δp 21MPa (210 bar)	HC	HC	HC	HC	HC	HC = fib. 12 μm(β) 210 bar	
		HD = fiber 21 μm(β) β>1.000 Δp 21MPa (210 bar)	HD	HD	HD	HD	HD	HD = fib. 21 μm(β) 210 bar	
		CC = cellulose 10 μm β>2 Δp 2MPa (20 bar)	CC	CC	CC	CC	CC	CC=cel.10 μm 20 bar	
		CLOGGING INDICATORS							
		03 = port, plugged	03	03	03	03	03	When the filter is ordered with FKM seals, the first digit of the indicator code is a letter (please see page 182 - 183).	
		5E = visual differential 500 kPa (5 bar)	5E	5E	5E	5E	5E		
		5F = visual differential 800 kPa (8 bar)	5F	5F	5F	5F	5F		
		6E = electrical differential 500 kPa (5 bar)	6E	6E	6E	6E	6E		
		6F = electrical differential 800 kPa (8 bar)	6F	6F	6F	6F	6F		
		7E = indicator 6E with LED	7E	7E	7E	7E	7E	N.B. Indicator series 72 & 73 only on request	
		7F = indicator 6F with LED	7F	7F	7F	7F	7F		
		T2 = elect. diff. 500 kPa (5 bar) with thermostat 30°C	T2	T2	T2	T2	T2		
		T3 = elect. diff. 800 kPa (8 bar) with thermostat 30°C	T3	T3	T3	T3	T3		
X	X	ACCESSORIES							
		XX= no accessory available	XX	XX	XX	XX	XX		

FILTER ELEMENT

	A	B	C	kg media F+ & C+	kg media H+	Area (cm ²)		
						Media F+	Media H+	Media C+
EPB11	45	25	85	0,15	0,25	355	340	310
EPB12	45	25	116	0,20	0,55	500	475	435
EPB13	45	25	211	0,30	0,45	935	915	815
EPB21	52	23,5	115	0,25	0,40	975	975	780
EPB22	52	23,5	210	0,35	0,55	1.830	1.785	1.465

