



TECHNICAL DATA

Aluminum Body Pressure Rating: 210 bar

Steel Body Pressure Rating: 350 bar

Cavity:

Refer to 16W2

* Refer to Winner Cartridge Valves Catalog.

Aluminum	0.8 kg(WITHOUT VALVES)
Steel	2.3 kg(WITHOUT VALVES)

* If you need the special specification.
Please contact us.

X	PORT SIZE		
	PORT 1	PORT 2	
G08	G 1"	G 1"	
P06	3/4"PT	3/4"PT	
P08	1"PT	1"PT	
S12	SAE 12	SAE 12	
S16	SAE 16	SAE 16	

Y	BODY MATERIAL	
A	HIGH-STRENGTH ALUMINUM	
T	STEEL (black oxide)	

Z	CARTRIDGE VALVES SELECTION
	WITHOUT VALVE
CV2003	CV16W2003N (90LPM , 240bar)
NV0N	NV16W20NL (350bar)
EP01	EP16W2A01N05 , 150LPM,350bar (NORMALLY CLOSED,WITHOUT COIL)
EP02	EP16W2A02N05 , 150LPM,350bar (NORMALLY OPEN,WITHOUT COIL)
COIL MUST BE ORDERED SEPARATELY (REFER TO EC-04W-X-Y-Z)	