

G5 Transmitters Pocket

Product description

- Light weight, water and impact resistant.
- 3-8 pushbuttons.
- 5 LED for machine and status feedback.
- Powered with 3 AAA batteries.
- Belt clip for convenient attachment on the operators belt.

Illustration



Technical data

Platform	G5
Power Supply	3 x AAA batteries
IP-Class	IP67
LED for feedback	From left: Green, Yellow, Yellow, Yellow, Red
Radio Frequency	2.4 GHz using frequency jumping technology
Operating range	> 100m > ~330 ft
Current consumption	10-60mA (depending on the number of LED used)
Operating time	Several months(depening of usage and application)
Approvals	TR05 Integrated duplex radio ISM-band, R&TTE, FCC and IC approved
Ambient Temperature	-25°C to +70°C ~ -15°F to +160°F
WxHxD	67 x 115 x 38 mm ~ 2.6 x 4.5 x 1.5 in
Weight	160 g (including batteries) ~ 0.35 lbs (including batteries)

Order information

Part number	Descripton
49281	G5-P3A - 3 pushbuttons labeled 1-3
50773	G5-P3CUSTOM - 3 pushbuttons w/o marking and w/o label.
49282	G5-P4A - 4 pushbuttons labeled IN, ON, OUT, OFF
50774	G5-P4CUSTOM - 4 pushbuttons w/o marking and w/o label.
49283	G5-P6A - 6 pushbuttons labeled 1-6
50775	G5-P6CUSTOM - 6 pushbuttons w/o marking and w/o label.
49110	G5-P8A - 8 pushbuttons labeled 1-8
49112	G5-P8B - 8 pushbuttons labeled 1-6, ON, OFF
49284	G5-P8C - 8 pushbuttons labeled 1-6, Fn, STOP
50776	G5-P8CUSTOM - 8 pushbuttons w/o marking and w/o label.

