




SCHEMA IDRAULICO / HYDRAULIC CIRCUIT




CODICE ORDINAZIONE ORDERING CODE

01	02	03	04	05
VBCL				

01	VALVOLE DI BILANCIAMENTO SINGOLE PER CENTRO APERTO (SINGLE COUNTERBALANCE VALVES FOR OPEN CENTER)					VBCL
02	DIMENSIONE (SIZE)	BSPP 1/4				140
		BSPP 3/8				380
		BSPP 1/2				120
		BSPP 3/4				340
03	MOLLA (SPRING) 30/210 bar (435/3045 PSI)	Rp 1:4.25	140 380	78 bar/al giro (1131 PSI/turn)	Taratura standard (Std. setting)	1
		Rp 1:8.75	120	160 bar/al giro (2320 PSI/turn)	Q=5 l/min 200 bar (2900 PSI)	
	MOLLA (SPRING) 60/350 bar (870/5075 PSI)	Rp 1:4.25	140 380	135 bar/al giro (1958 PSI/turn)	Taratura standard (Std. setting)	2
		Rp 1:8.75	120	160 bar/al giro (2320 PSI/turn)	Q=5 l/min 350 bar (5075 PSI)	
	MOLLA (SPRING) 60/350 bar (870/5075 PSI)	Rp 1:6.2	340	143 bar/al giro (2074 PSI/turn)	Taratura standard (Std. setting)	
		Rp 1:10.6		242bar/al giro (3509 PSI/turn)	Q=5 l/min 350 bar (5075 PSI)	
04	MATERIALE (MATERIAL)	Acciaio + zincatura (Steel body + zinc-plating)				S
		Acciaio + zinco-nichel (Steel body + zinc-nickel)				K
05	RAPPORTO DI PILOTAGGIO (PILOT RATIO)	140 380 120	1:4.25 Standard			/
			1:8.75			8
			1:6.2			/
		340	1:10,6			11


Opzione: Tappo piombatura - Optional: Tamper proof cap **81300095**

PERFORMANCES



DATI TECNICI / TECHNICAL DATA

Oil hydraulic - Mineral oil	ISO 6743/4 (DIN 51524)
Viscosità olio - Oil viscosity	15-250 mm²/s (15 to 250 cSt)
Classe di contaminazione max Max contamination index	ISO 4406:1999 Classe 18/16/13
Temperatura dell'olio - Oil temperature	-20°C +80°C -4°F +176°F
Temperatura ambiente - Environment temperature	-20°C +50°C -4°F +122°F
È indispensabile l'utilizzo di un filtro per proteggere la valvola (filtrazione consigliata 15 µm) It is necessary a filter use to protect the valve (advised filtration 15 µm)	
Trafilamento@46cSt & 200 bar Leakage@46cSt & 200 bar	0,25 cm³/min - 5 gocce/min 0,015 in³/min - 5 drops/min



CARATTERISTICHE TECNICHE / TECHNICAL CHARACTERISTICS

TIPO TYPE	A	PORTATA MAX MAX FLOW l/min-USgpm	PRESSIONE MAX MAX PRESSURE bar-PSI	B	C	D	E	F	G	H	L	M	N	O	S	PESO APPROX (kg) APPROX WEIGHT (lbt)
VBCL140	BSPP 1/4	30 (7.9)	350 (5075)	29 (1.14)	49 (1.93)	23 (0.91)	81 (3.19)	51 (2.01)	81 (3.19)	66 (2.60)	95 (3.74)	6,5 (0.26)	36 (1.42)	33 (1.30)	6,5 (0.26)	0,98 (2.16)
VBCL380	BSPP 3/8	40 (10.6)			59 (2.32)	21 (0.83)	84 (3.30)		84 (3.31)	67,5 (2.66)	100 (3.94)	9,5 (0.37)	40 (1.57)			0,92 (2.02)
VBCL120	BSPP 1/2	60 (15.9)			69 (2.72)	20 (0.79)	120 (4.72)		120 (4.72)	96 (3.78)	140 (5.51)	50 (1.97)	45 (1.77)			1,09 (2.40)
VBCL340	BSPP 3/4	120 (31.7)			39 (1.54)	20 (0.79)	120 (4.72)		120 (4.72)	96 (3.78)	140 (5.51)	50 (1.97)	45 (1.77)			2,54 (5.59)