

Alpha series - Front end cylinder with outer cover





FC A169-5-06050-000-K0343-HD

Item no.

70516500

Tipping weight

45 - 57 ton



* incl. 20 [-5; +30] mm pull out

3D model is available on request

Specifications

Max. working pressure	250 bar
Weight	332 kg
Working volume	83 L
Total volume	90 L
Max. cyl. load (start tipping)	245 kN

Max. pump flow

With KO ¹	195 L/min
Without KO ¹	137 L/min
With KO ¹ below -20°C	137 L/min
Without KO ¹ below -20°C	96 L/min

Tipping time

With KO ¹	26 sec
Without KO ¹	36 sec
With KO ¹ below -20°C	37 sec
Without KO ¹ below -20°C	51 sec
Allowable lowering time	20 sec

Extension	1	2	3	4	5	6	7	Total
Effective diameter [mm]	169	149	129	110	91			6050
Stroke* [mm]	1185	1210	1215	1220	1220			

Technical notes

• This cylinder is a lifting device only. • It should not be used as a structural member and should not be subjected to side loads. • Tipping valve must have a pressure relief at the cylinder port set not higher than max. working pressure. • Verify max. cyl. load. • Working temperature range is between -40°C and +80°C. • Max. duration of extension is 0.5 hours (excluded hard chromed stages). • Cylinder is painted black (RAL9005) with a min. thickness conforming to the 480 hours neutral salt spray test as per ISO 9227. • ¹ Hyva knock-off.


Related documentation

Bracket options: 015BRA10 & 015BRA12

Mounting instructions: CYL-0030

Oil specifications: OIL-0011
Spec sheet explanation: CYL-0041

Tipping weight



BL	body length
OH	rear overhang
Ycog	vert. pos. centre of gravity
Qo	pivot length
C	bracket length
At	tipping angle
	stroke x 60 / Qo

BL [mm]	8100			7650			7200		
OH [mm]	200	500	800	200	500	800	200	500	800
At [°]	44	46	48	47	49	51	50	52	55
Ycog [mm]									
600	45	49	53	47	51	57	50	55	
900	48	52		51					
1200	52								

Tipping weight [ton] at maximum pressure of 250 bar for a vertically mounted cylinder and C is 229 mm

For detailed tipping calculations please refer to: <https://tipper.hyva.com>

Alpha series - Front end cylinder with outer cover



FC A169-5-06050-000-K0343-HD

Item no.

70516500

Pos.	Part no.	Description	Qty.
C01	71839050	DUST COVER FC LOW 15-273	1
C02	71737484	COVER 273-1245 PIN60 A360 SPH LOCK	1
C03	01702956 K	WASHER M48 DIN 125B ZP	1
C04	01702907 K	TOPNUT NYLOC M48x3 DIN 985 ZP	1
C05	01791953	O-RING COVER D.273	1
C06	15014550 K	BOLT HSHC M12X30X1.75 Q8.8 DIN 912 ZP	1
P01	74412441	PISTON FL2 S 091-1445-HD-HC	1
P02	71807093 K	SLIDER FL 091 (2 X 1/2) A35	1
P03	71851091 K	OUTER STOPRING FL 091 A22	2
P04	71822705	BOTTOM PLATE PISTON FL 091 MK2 HD	1
P05	01745020 K	CIRCLIP 78 DIN 472 (82.5x2.5)	1
P06	71870215 K	O-RING PISTON BOTTOM 091	1
P07	71848200	PISTON HEAD FL 091 MK2	1
P08	01226430 K	O-RING 72.62 X 3.53 MM	1

S41	74613440	STAGE FL2 110-1440-HD	1
S42	71808110 K	PACKSET FL 110/HP 110 TANDEM SEAL	1
S43	71807112 K	SLIDER FL 110 (2 X 1/2) A35	1
S44	71851110 K	OUTER STOPRING FL 110 A22	2
S45	71852110 K	LIFTRING FL 110 A22	1

S31	74614440	STAGE FL2 129-1440-HD	1
S32	71808129 K	PACKSET FL 129/HP 129 TANDEM SEAL	1
S33	71807131 K	SLIDER FL 129 (2 X 1/2) A35	1
S34	71851129 K	OUTER STOPRING FL 129 A22	2
S35	71852129 K	LIFTRING FL 129 A22	1




S21	74615440	STAGE FL2 149-1440-HD	1
S22	71808149 K	PACKSET FL 149/HP 150 TANDEM SEAL	1
S23	71807151 K	SLIDER FL 149 A35	1
S24	71851149 K	OUTER STOPRING FL 149 A22	2
S25	71852149 K	LIFTRING FL 149 A22	1

S11	74616440	STAGE FL2 169-1440-HD	1
S12	71808169 K	PACKSET FL 169 TANDEM SEAL	1
S13	71807171 K	SLIDER FL 169 A35	1
S14	71851169 K	OUTER STOPRING FL 169 A22	1
S15	71852169 K	LIFTRING FL 169 A22	1

B01	74517440R1145	BASE FL2 191-1483-4/4BSAE-190-C273-HD	1
B02	71802191 K	PACKSET FL 191	1
B03	71825430	BOTTOM PLATE FL2 191	1
B04	71870040 K	SEAL BOTTOM PLATE FL 191	1
B05	71820195	LOCKING PLATE FL2 191	3
B06	01732055 K	BOLT HEX M8X20X1.25 SET 6 PCS	1
B07	01732559 K	WASHER SPRING M8 SET 6 PCS	1

Seal kit complete

	71908651 K	Consists of all packsets with packset grease and O-rings	
--	------------	--	--



Notes

The inner stopring is pre-mounted in the grooves on spare bases and stages. Therefore, when ordering new tubes, it is not required to order inner stoprings separately.

For repair instructions see: CYL-0040. Serial no. is located on type plate and near type plate support.